

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture AMBERCLENS FG

Registration number -

Synonyms None.

Product code BDS000316AE

Issue date 11-June-2021

Version number 01

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cleaners - Precision

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company name CRC Industries UK Ltd.
Address Wylids Road
 Castlefield Industrial Estate
 TA6 4DD Bridgwater Somerset
 United Kingdom
Telephone +44 1278 727200
Fax +44 1278 425644
E-mail hse.uk@crcind.com
Website www.crcind.com

Company name CRC Industries Europe bv
Address Touwslagerstraat 1
 9240 Zele
 Belgium
Telephone +32(0)52/45.60.11
Fax +32(0)52/45.00.34
E-mail hse@crcind.com
Website www.crcind.com

1.4. Emergency telephone number Tel.:(+44)(0)1278 72 7200 (office hours)

General in EU 112 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Austria National Poisons Information Centre +431 406 4343 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Belgium National Poisons Control Center 070 245 245 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Bulgaria National Toxicological Information Centre +359 2 9154233 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Czech Republic National Poisons Information Centre +420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Denmark National Poisons Control Center +45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Estonia National Poisons Information Centre 16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be available for the Emergency Service.)

Finland National Poison Information Center	(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
France National Poisons Control Center	ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Hungary National Emergency Phone Number	36 80 20 11 99 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Lithuania Neatidėliotina informacija apsinuodijus	+370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
Malta Accident and Emergency Department	2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
Netherlands National Poisons Information Center (NVIC)	030-274 88 88 (Only for the purpose of informing medical personnel in cases of acute intoxications)
Norway Norwegian Poison Information Center	22 59 13 00 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Romania Biroul RSI si Informare Toxicologica	021.318.36.06 (Available 8:00AM-3:00PM. SDS/Product information may not be available for the Emergency Service.)
Slovakia National Toxicological Information Centre	+421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Sweden National Poison Information Center	112 - and ask for Poison Information (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.


Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards		
Aerosols	Category 3	H229 - Pressurized container: May burst if heated.
Health hazards		
Serious eye damage/eye irritation	Category 1	H318 - Causes serious eye damage.

Hazard summary Aerosol CONTENTS UNDER PRESSURE.
Pressurised container may explode when exposed to heat or flame. Causes serious eye damage. Occupational exposure to the substance or mixture may cause adverse health effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains:	Decyl alcohol, ethoxylated
Hazard pictograms	
Signal word	Danger
Hazard statements	
H229	Pressurized container: May burst if heated.
H318	Causes serious eye damage.

Precautionary statements

Prevention	
P102	Keep out of reach of children.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P251	Do not pierce or burn, even after use.
Response	
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P313	Get medical advice/attention.

Storage

P410 + P412

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

P501

Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information

7% by mass of the contents are flammable.

Regulation (EC) No 648/2004 on detergents:

aliphatic hydrocarbons <5%

anionic surfactants <5%

non-ionic surfactants <5%

benzisothiazolinone, methylisothiazolinone, methylchlorisothiazolinone

2.3. Other hazards

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****General information**

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Decyl alcohol, ethoxylated	1 - 5	26183-52-8 500-046-6	-	-	
Classification: Acute Tox. 4;H302;(ATE: 500 mg/kg), Eye Dam. 1;H318					A
Dipropylene glycol monomethyl ether	1 - 5	34590-94-8 252-104-2	01-2119450011-60	-	#
Classification: -					

List of abbreviations and symbols that may be used above

Note A: Not registered due to polymer status (no longer polymer list - directive 92/32/EEC).

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments

The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures**General information**

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

4.1. Description of first aid measures**Inhalation**

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

Ingestion

In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth.

4.2. Most important symptoms and effects, both acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures**General fire hazards**

Not available.

5.1. Extinguishing media**Suitable extinguishing media**Water fog. Foam. Dry chemical powder. Carbon dioxide (CO₂).**Unsuitable extinguishing media**

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters**Special protective equipment for firefighters**

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures

Containers should be cooled with water to prevent vapour pressure build up.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

For emergency responders

Keep unnecessary personnel away. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. This product is miscible in water. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Do not re-use empty containers. Do not get this material in contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store away from incompatible materials (see Section 10 of the SDS).

Storage class (TRGS 510): 2B (Aerosol dispensers and lighters)

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits****Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001**

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	Ceiling	614 mg/m ³
		100 ppm
	MAK	307 mg/m ³ 50 ppm

Belgium. Exposure Limit Values

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m ³
		50 ppm

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m ³
		50 ppm

Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	MAC	308 mg/m ³
		50 ppm

Czech Republic. OELs. Government Decree 361

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	Ceiling	550 mg/m ³
	TWA	270 mg/m ³

Denmark. Exposure Limit Values

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TLV	309 mg/m ³
		50 ppm

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances (Regulation No. 105/2001, Annex), as amended

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m ³
		50 ppm

Finland. Workplace Exposure Limits

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	310 mg/m ³
		50 ppm

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	VME	308 mg/m ³
	Regulatory status: Regulatory binding (VRC)	50 ppm
	Regulatory status: Regulatory binding (VRC)	

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Type	Value	Form
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	310 mg/m ³	Vapour.
		50 ppm	Vapour.

Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace

Components	Type	Value	Form
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	AGW	310 mg/m ³	Vapour and aerosol.
		50 ppm	Vapour and aerosol.

Greece. OELs (Decree No. 90/1999, as amended)

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	STEL	900 mg/m ³
		150 ppm

Greece. OELs (Decree No. 90/1999, as amended)

Components	Type	Value
	TWA	600 mg/m3 100 ppm

Hungary. OELs. Joint Decree on Chemical Safety of Workplaces

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m3

Iceland. OELs. Regulation 154/1999 on occupational exposure limits

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	300 mg/m3 50 ppm

Ireland. Occupational Exposure Limits

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m3 50 ppm

Italy. Occupational Exposure Limits

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m3 50 ppm

Latvia. OELs. Occupational exposure limit values of chemical substances in work environment

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m3 50 ppm

Lithuania. OELs. Limit Values for Chemical Substances, General Requirements

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	STEL	450 mg/m3
	TWA	75 ppm 308 mg/m3 50 ppm

Luxembourg. Binding Occupational exposure limit values (Annex I), Memorial A

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m3 50 ppm

Netherlands. OELs (binding)

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	300 mg/m3

Norway. Administrative Norms for Contaminants in the Workplace

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TLV	300 mg/m3
		50 ppm

Poland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	STEL	480 mg/m3
	TWA	240 mg/m3

Portugal. OELs. Decree-Law n. 290/2001 (Journal of the Republic - 1 Series A, n.266)

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m3
		50 ppm

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	STEL	150 ppm
	TWA	100 ppm

Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m3
		50 ppm

Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m3
		50 ppm

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m3
		50 ppm

Spain. Occupational Exposure Limits

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m3
		50 ppm

Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	STEL	450 mg/m3
		75 ppm
	TWA	300 mg/m3

Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)

Components	Type	Value
		50 ppm

Switzerland. SUVA Grenzwerte am Arbeitsplatz

Components	Type	Value	Form
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	STEL	300 mg/m3	Vapour and aerosol.
	TWA	50 ppm	Vapour and aerosol.
		300 mg/m3	Vapour and aerosol.
		50 ppm	Vapour and aerosol.

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m3

50 ppm

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m3

50 ppm

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no effect levels (DNELs)

General Population

Components	Value	Assessment factor	Notes
Dipropylene glycol monomethyl ether (CAS 34590-94-8)			
Long-term, Systemic, Dermal	121 mg/kg bw/day	16,8	Repeated dose toxicity
Long-term, Systemic, Inhalation	37,2 mg/m3		Repeated dose toxicity
Long-term, Systemic, Oral	0,33 mg/kg bw/day	600	Repeated dose toxicity

Workers

Components	Value	Assessment factor	Notes
Dipropylene glycol monomethyl ether (CAS 34590-94-8)			
Long-term, Systemic, Dermal	283 mg/kg bw/day	10,08	Repeated dose toxicity
Long-term, Systemic, Inhalation	308 mg/m3		Repeated dose toxicity

Predicted no effect concentrations (PNECs)

Components	Value	Assessment factor	Notes
Dipropylene glycol monomethyl ether (CAS 34590-94-8)			
Freshwater	19,2 mg/l	100	
Intermittent releases	192 mg/l	10	
Marine water	1,92 mg/l	1000	
Sediment (freshwater)	70,2 mg/kg		
Soil	2,74 mg/kg		

Exposure guidelines

EU Exposure Limit Values: Skin designation

Dipropylene glycol monomethyl ether (CAS 34590-94-8) Can be absorbed through the skin.

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Dipropylene glycol monomethyl ether (CAS 34590-94-8) Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering controls Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

General information	Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.
Eye/face protection	Wear safety glasses with side shields (or goggles) and a face shield. Use eye protection conforming to EN 166.
Skin protection	
- Hand protection	When handling the product wear chemical-resistant gloves (standard EN 374). The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Nitrile gloves are recommended. Suitable gloves can be recommended by the glove supplier.
- Other	Not available.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with organic vapour cartridge. (Filter type ABEK)
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
Hygiene measures	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Form	Aerosol
Colour	White.
Odour	Neutral.
Melting point/freezing point	-182 °C (-295,6 °F) estimated
Boiling point or initial boiling point and boiling range	100 °C (212 °F)
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Flash point	None
Auto-ignition temperature	> 200 °C (> 392 °F)
Decomposition temperature	Not available.
pH	11
Solubility(ies)	
Solubility (water)	Soluble in water
Vapour pressure	3000 hPa estimated
Vapour pressure temp.	20 °C (68 °F)
Vapour density	Not available.
Relative density	1,01 g/cm ³
Relative density temperature	20 °C (68 °F)
Particle characteristics	Not available.

9.2 Other safety characteristics

Aerosol spray enclosed space

Deflagration density > 300 s/m³

Aerosol spray ignition distance < 15 cm

Chemical family Cleaner

Evaporation rate Not available.

Explosive properties Not explosive.

Heat of combustion (NFPA 30B) 1,25 kJ/g estimated
 Oxidising properties Not oxidising.
 VOC 69 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.
 10.2. Chemical stability Material is stable under normal conditions.
 10.3. Possibility of hazardous reactions No dangerous reaction known under conditions of normal use.
 10.4. Conditions to avoid Avoid high temperatures.
 10.5. Incompatible materials Strong oxidising agents.
 10.6. Hazardous decomposition products Carbon oxides.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.
 Skin contact Based on available data, the classification criteria are not met.
 Eye contact Causes serious eye damage.
 Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

Symptoms Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

11.1. Information on toxicological effects

Acute toxicity Classification based on calculation method. Based on available data, the classification criteria are not met.

Product	Species	Test Results
AMBERCLENS FG		
Acute		
Dermal		
LD50	Rabbit	245 g/kg
Oral		
LD50	Rat	106 g/kg

Components	Species	Test Results
Dipropylene glycol monomethyl ether (CAS 34590-94-8)		
Acute		
Dermal		
LD50	Rabbit	9510 mg/kg
Oral		
LD50	Rat	5000 mg/kg

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Causes serious eye damage.

Respiratory sensitisation Based on available data, the classification criteria are not met.

Skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Not listed.

Reproductive toxicity Based on available data, the classification criteria are not met.

Specific target organ toxicity - single exposure Based on available data, the classification criteria are not met.

Specific target organ toxicity - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Not likely, due to the form of the product.

Mixture versus substance information Not available.

11.2. Information on other hazards

Endocrine disrupting properties The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Other information Not available.

SECTION 12: Ecological information

12.1. Toxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
Dipropylene glycol monomethyl ether (CAS 34590-94-8)		
Aquatic		
<i>Acute</i>		
Algae	EC50	Algae 969 mg/l, 96 h
Crustacea	EC50	Daphnia 1919 mg/l, 48 h
Fish	LC50	Fish 10000 mg/l, 96 h
<i>Chronic</i>		
Crustacea	NOEC	Daphnia 0,5 mg/l, 22 d

12.2. Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

Dipropylene glycol monomethyl ether 0,004

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB assessment This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.

12.6. Endocrine disrupting properties None known

12.7. Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation potential.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

EU waste code The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

Special precautions Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number UN1950

14.2. UN proper shipping name AEROSOLS

14.3. Transport hazard class(es)

Class 2.2

Subsidiary risk -

Hazard No. (ADR) Not available.
Tunnel restriction code (E)
ADR/RID - Classification 5A
code:

14.4. Packing group Not applicable
14.5. Environmental hazards No
14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.
for user

IATA

14.1. UN number UN1950
14.2. UN proper shipping AEROSOLS
name
14.3. Transport hazard class(es)
Class 2.2
Subsidiary risk -
14.4. Packing group Not applicable
14.5. Environmental hazards No
14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.
for user

IMDG

14.1. UN number UN1950
14.2. UN proper shipping AEROSOLS
name
14.3. Transport hazard class(es)
Class 2.2
Subsidiary risk -
14.4. Packing group Not applicable
14.5. Environmental hazards
Marine pollutant No
EmS F-D, S-U
14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.
for user

14.7. Maritime transport in bulk Not established.
according to IMO instruments

ADR; IATA; IMDG



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

National regulations

This safety data sheet conforms to the following laws, regulations and standards:

Act on the management of packaging and packaging waste of June 13, 2013
Regulation of the Minister of Health of June 11, 2012 on the categories of dangerous substances and dangerous preparations whose packaging should be fitted with child-resistant closures and a tactile warning of danger
REGULATION OF THE MINISTER OF HEALTH of February 2, 2011 on tests and measurements of factors harmful to health in working environments
Regulation of Ministry of Labor and Social Policy of June 6, 2014. On the matter of maximum permissible concentrations and intensities of harmful factors in the work environment (Journal of Laws 2014, item. 817)
Chemical Safety at Workplace Ordinance Joint Decree No. 25/2000 (Annex 2): Permissible limit values of biological exposure (effect) indices Decree No. 25/2000. (IX. 30.) EüM-SzCsM of the Minister of Health and the Minister of Social and Family Affairs on chemical safety at work Act No. 93 of 1993 on Labour Safety (1993.évi XCIII.), as amended
Government Decree No. 220 of 2004 (VII. 21.) providing rules on the protection of surface waters quality
Government Decree No. 98/2001 (VI. 15.), on the conditions of the activities related to hazardous waste, and Ministry of Environmental Affairs Decree No. 16/2001 (VII. 18.), on the register of waste s Public Act No. XXV of 2000 on Chemical Safety, and Application Decree No. 44/2000. (XII.27.) EüM [of the Ministry of Health]
Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.
AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).
ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).
CAS: Chemical Abstract Service.
Ceiling: Short Term Exposure Limit Ceiling value.
CEN: European Committee for Standardization.
CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures.
GWP: Global Warming Potential.
IATA: International Air Transport Association.
IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.
IMDG: International Maritime Dangerous Goods.
MAC: Maximum Allowed Concentration.
MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG).
MARPOL: International Convention for the Prevention of Pollution from Ships.
PBT: Persistent, bioaccumulative and toxic.
REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals).

RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer).

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit.

TLV: Threshold Limit Value.

TWA: Time Weighted Average.

VLE: Exposure Limit Value.

VME: Exposure Average Value.

VOC: Volatile organic compounds.

vPvB: Very persistent and very bioaccumulative.

STEL: Short-term Exposure Limit.

Not available.

References

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any H-statements not written out in full under Sections 2 to 15

H302 Harmful if swallowed.

H318 Causes serious eye damage.

Revision information

None.

Training information

Follow training instructions when handling this material.

Disclaimer

CRC Industries Europe UK Limited cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.